



DURABOOK Tough Features

Drop Resistant	Magnesium alloy case - 20 times stronger than ABS plastic, offering higher survival rate after drops and bumps. 26 drops from 76 cm height to plywood over concrete with unit off and display closed. 5 units to pass. Simulate MIL STD 810G Method 516.6, Procedure IV.
Shock Resistant	Anti-shock mounting design protects LCD screen and hard disk drive from damage and data loss. Flexible HDD cable design absorbs shock from drops. Simulate MIL STD 810G Method 514.6, Procedure I, Category 24, Fig 514.6 E-1/ASTM4169, Truck Transport, 11.5.2 Random test, Assurance Level II
Spill Resistant	Spill resistant keyboard, touchpad and buttons. Spill resistant design stops spills from leaking into sensitive interior parts.
Optical Disk Lock	Exclusive optical disk tray lock prevent unintentional tray eject from drop and vibration.
Battery Protection	Double protection smart battery circuitry prevents damage caused by current or voltage surges and overheating. Smart Battery Calibration helps fight the loss of battery capacity after repeated charge-discharge cycles.

System Specifications

Processor	Intel® Core™ 2 Duo processor (FSB 800/667MHz) 4MB L2 Cache Intel® Celeron® M processor (FSB 533MHz) 2MB L2 Cache		
Chipset	North Bridge: Intel® GME 965	South Bridge: Intel® ICH8M	
System Memory	Two Dual Channel DDR II SODIMM Slots each for 512MB/1GB/2GB (Max. 4GB) *Max. 3GB under Windows XP & Vista 32bit OS		
Hard Disk Drive	2.5" 9.5mm high Hard Disk Drive, 250/320GB SATA 150 Anti Shock Mounted HDD (Safety of Vibration & Transporting)		
Optical Media Device	One internal optical drive for: • DVD Dual or DVD Super Multi (DVD-R/CD-RW/DVD-RW/DVD+RW_DL/DVD-RAM)		
Display	15.4" WXGA resolution (1280 x 800)		
Graphics & Video	Intel® GME 965 built-in (Intel® Media Accelerator GMA X3100) • Intel® enhancement AGP BUS equivalent hardware 2D/3D video graphic accelerators • Shared system memory up to 358MB Max. (Intel Driver Dynamic Changed)		
Audio	Compliant to Intel® High Definition Audio • Stereo: two 1.5W speakers • Build in stereo Mic. Array		
I/O Devices	• One Smart card socket • 4 in 1 media card reader support MS/MS Pro/SD/MMC	• One 1.3 Mega-pixel Webcam	
I/O Ports	• Three USB 2.0 connectors • One IEEE 1394 port • One 9 pin D-sub connector for RS232 serial port • One Type II Express Card 34/54 • One 15 pins D-Sub connectors for external monitor	• One Line-Out phone jack for external speakers • One Mic-In phone jack for external microphone • One RJ-11 jack for internal 56Kbps V.90 modem • One RJ-45 jack for internal 10/ 100/ 1000Mbps Ethernet • One DC-In jack	
Keyboard	Spill resistant Keyboard (88 Keys with Windows Key) Function Keys: • Fn+F1: Bluetooth off/on • Fn+F2: 3G off/on • Fn+F3: Touchpad off/on • Fn+F4: Suspend mode • Fn+F5: Display Switch (LCD -> CRT -> LCD+CRT)		• Fn+F6: Brightness Decrease • Fn+F7: Brightness Increase • Fn+F8: Volume Control Down • Fn+F9: Volume Control Up • Fn+F10: Mute
Wireless/Communications	Modem: Internal 56K V.92 Fax/Modem Ethernet: Integrated 10/100/1000 Mbps Ethernet Wireless: Intel® Wireless WiFi Link 4965AGN (802.11a/b/g/n) Bluetooth EDR 2.0 and upper (optional)		
AC Adapter	Input: AC 90~265V 47/63Hz, Output: 19V/4.74A/65W		
Battery	Standard: 9 cells 6600mAh Li-Ion battery (Approx. 4hrs) Optional: 6 cells 4400mAh Li-Ion battery (Approx. 3hrs)		
Dimensions & Weight	370mm (W) X 276mm (D) X 37.5~40mm (H) 3.1 Kg/7.1lbs (with 9 cell battery) 2.9Kg/6.6lbs (with 6 cell battery)		
Certification	FCC, DOC, CUL CE, CB		
Security	Kensington Lock / Administrator password / Boot password		

• The specification and pictures are subject to change without notice.
• All brand names are registered trademarks of their respective owners.



Taipei (Headquarters)
Twinhead International Corporation
10F, 550, Rueiguang Road,
Neihu, Taipei, 114, Taiwan, R.O.C.
Tel : 886-2-5589-9999
Fax: 886-2-5555-7777
<http://www.twinhead.com>

U.S.A.
GammaTech Computer Corp.
48303 Fremont Blvd.
Fremont, CA94538, U.S.A.
Tel : 1-510-492-0828
Fax: 1-510-492-0820

Germany
Twinhead GmbH
Nikolaus-Otto-Strasse 4
40670 Meerbusch-Osterath Germany
Tel : +49 (0)2159-6944-0
Fax: +49 (0)2159-6944-20
<http://www.twinhead.de>

