



Rugged DC/DC Auto Power Adapter

for Xplore Tecchnologies Tablet PC

20.0V @ 3.5A

70Watt

The Lind Automobile Power Adapter delivers a true continuous 70 Watt power output to your Xplore Technologies Tablet PC. The Adapter allows the Tablet PC to be operated and its internal battery to be recharged from any (12-16V) 12-32 VDC source. Simply plug the Lind Automobile Power Adapter into the cigarette lighter socket in an automobile and into the power jack of the Tablet PC. The adapter adjusts, conditions and regulates the power from the input to the correct DC voltage required for the Tablet PC.



Voltage spikes or surges occurring on the voltage line will be filtered by the adapter eliminating

the possibility of damage to the Tablet PC due to supply voltage variations. The Lind Automobile Power Adapter is epoxy potted and housed in a recently developed ABS case for durability and sealed to protect the Adapter from moisture and high humidity (IP54).

Part number:

12-16V input: [XP2035-940](#)

12-32V input: [XP2035-1385](#)

Technical Information

INPUT VOLTAGE	(12 to 16) 12 to 32 VDC
OUTPUT VOLTAGE	20,0 VDC
OUTPUT CURRENT	3.5 A max.
WEIGHT	290 gram
SIZE	13.0 x 6.0 x 2.2 cm
INPUT CABLE	92cm, 18 awg, Cig Plug
OUTPUT CABLES	92cm, 20 awg, DC Plug
INPUT FUSE	15 A inside adapter
WARRANTY	3 Year
OPERATING TEMPERATURE	-20 to +40 °C
STORAGE TEMPERATURE	-40 to +85 °C

Safety Information

- Output Short Circuit Shut Down
- Output Over Current Shut Down
- Output High Voltage Limit
- Input Power Limit
- Input Reverse Polarity Protection
- Over Temperature Shut-Down
- Low Input Voltage Shut-Down
- High Input Voltage Shut-Down
- Automatic Reset of Safety Shut-Down
- On-Board Fuse Link



6414 Cambridge Street
Minneapolis, MN
55426
USA

Phone: +1 (952) 927 6303
Fax: +1 (952) 927 7740
Email: europa@lindelectronics.com
Web: www.lindelectronics.com